

VegaIP200 Data Sheet



The Vega 200 can be used with various combinations of telephony ports. It supports various technologies (PRI, BRI, Analog, SIP, IAX) with up to 200 Users (SIP ext, Analog ext ports). The units are available in a standard 19" 2U rack/wall-mountable chassis.

Features

access

- Proxy
 - User friendly Web Interface
 - Web Phone
 - Interface in Different Languages
 - web chat
 - CDR (Call Details Record) via Web
 - IM (Instant Messaging Server)
-
- Call center
 - TDM/SIP/IAX Trunks
 - Conference Rooms
 - Remote Extensions
 - URI based calls (dial by email address)
 - Voicemail
 - Follow-Me
 - Fax 2Mail
 - Time-Based Routing
 - Mail2Fax
 - Advanced Dialing Rules
 - Unified Messaging
 - Music-On-Hold
 - IVR Menu System
 - Least Cost Routing
 - Ring Groups

- Web Access to Voicemail
- Call Queues
- Admin Status Screen
- Association of several alternative
- Package Manager (for easy updates)

internal and external addresses

- Network Settings Tool
- Video calls
- Phone Provisioning Tool
- DISA Features
- Echo Cancellation - OSLEC (Open Source Line Echo Cancellation)
- FIREWALL
- VPN (SSL, PPTP, IPsec, VNC, GRE)

Software

Operative System Distribution	Vega ver. 1.0
--------------------------------------	---------------

A product of Wisecom communications Ltd.


Hardware

Processor	Intel Atom D525 Dual Core 1.8 GHz
RAM	1 GB
Hard disk	From 250GB 2.5" (500GB optional)
USB	4 external USB 2.0

Telephony

Maximum number of concurrent calls	45
Maximum number of built-in analog ports	32 (additional ports with external Unibox units)
Number of E1 / T1 ports	2 (up to 45 concurrent calls)
Modules	<ul style="list-style-type: none"> • 8 FXS ports • 8 FXO ports • Up to 8 BRI ISDN ports • Up to 2 modules of PRI (up to 45 concurrent calls)

Power

Power supply	Internal
Voltage	Switching, auto adjust 110/220 Volts, 50/60 Hz
Power consumption	230 Watts (maximum)
Built in grounding connection	

Network

Ethernet port	10/100/1000 Mb/s
----------------------	------------------

Maintenance and Support

- Monitor and keyboard support
- Disaster Recovery utility provided on Disk-on-Key
- Secured connection remote maintenance/support
- Internet updates

Environment

Storage temperature	-20° to 70° Celsius (-4° -158° F)
---------------------	-----------------------------------

Working temperature	0° to 40° Celsius (32° -104° F)
Humidity	20%-95%, non condensing

Dimensions and Weight

Weight	8 Kg 18Lbs (weight depends on configuration)
Size	19" 2U industry standard rack-mountable chassis

Specifications may change without prior notice

